Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
L1	149	(headless or head?less) near3 (device or computer or PC or unit or server)	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2004/12/04 17:17
L2	15	1 same (request$4 or initiat$4) same (configur$7)	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2004/12/04 14:42
L3	5976	(headless or head?less or blind) near3 (device or computer or PC or unit or server)	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2004/12/04 14:42
L4	23	3 same (request$4 or initiat$4) same (configur$7)	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2004/12/04 14:45
L5	3	3 with (request$4 or initiat$4) with (configur$7)	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2004/12/04 14:44
L6	0	3 with (self?configur$7)	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2004/12/04 14:44
L7	3	(DHCP) with (alternate near3 address)	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2004/12/04 17:21
L8	81	(DHCP) with ((alternate or substitute or different) near3 address)	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2004/12/04 17:23
L9	6	(DHCP) with ((alternate or substitute) near3 address)	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2004/12/04 17:23

S1	121	(headless or head?less) near3 (device or computer or PC or unit)	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2004/12/03 17:44
S2	30	S1 with configur$7	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2004/12/03 17:54
S3	9	S1 with bootstrap	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2004/12/03 17:45
S4	149	(headless or head?less) near3 (device or computer or PC or unit or server)	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2004/12/03 17:44
S5	9	S4 with bootstrap	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2004/12/03 17:45
S6	4	("5216644" | "5748596" | "6125408" | "6345318").PN.	US-PGPUB; USPAT; USOCR	OR	ON	2004/12/03 17:57